

WHAT IS CLAIMED IS:

5

1. A magnetic recording medium comprising:
 - an in-plane magnetic film used for recording, the in-plane magnetic film having a magnetization easy axis in an in-plane direction; and
 - a perpendicular magnetic film formed on said in-plane magnetic film, the perpendicular magnetic film having a magnetization easy axis oriented in a direction perpendicular to said magnetization easy axis of said in-plane magnetic film,
 - wherein a tBr of said perpendicular magnetic film is set so as not to exceed one-fifth of a tBr of said in-plane magnetic film at the maximum, where the tBr is the product of a thickness and a residual magnetization.

25

2. The magnetic recording medium as claimed in claim 1, wherein said perpendicular magnetic film has a thickness not exceeding 5 nm at the maximum.

35

3. The magnetic recording medium as claimed in claim 1, wherein an anisotropic magnetic field H_k of said perpendicular magnetic film is set

at least 1.2 times as large as an anisotropic magnetic field H_k of said in-plane magnetic film.

5

4. The magnetic recording medium as
claimed in claim 1, further comprising a nonmagnetic
spacer provided between said in-plane magnetic film
10 and said perpendicular magnetic film.

15 5. The magnetic recording medium as
claimed in claim 4, wherein said nonmagnetic spacer
has a thickness not exceeding 2 nm.

20

6. The magnetic recording medium as claimed in claim 1, wherein said perpendicular magnetic film is formed of one of a Co-group alloy 25 and a Co-group artificial lattice film.

30 7. A magnetic recording and reproducing device including

a magnetic recording medium comprising:
an in-plane magnetic film used for
recording, the in-plane magnetic film having a
magnetization easy axis in an in-plane direction;
and

said in-plane magnetic film, the perpendicular magnetic film having a magnetization easy axis oriented in a direction perpendicular to said magnetization easy axis of said in-plane magnetic
5 film,

wherein a tBr of said perpendicular magnetic film is set so as not to exceed one-fifth of a tBr of said in-plane magnetic film at the maximum, where the tBr is the product of a thickness
10 and a residual magnetization.

00000000000000000000000000000000